

Safety data sheet

Teak Oil
(290/1290/30290)

1. Identification of the substance/preparation and of the company/undertaking

Prepared on: 09-09-2005/ MBM
Replaces: 18-12-2003

Product use: Cleans the surface of the teak, sets off veins, protects and maintains the teak

Supplier:

Sterling Polish Company A/S

Nybrovej 95

DK-2820 Gentofte

Tel:+45-45877044 Fax:+45-45930070

2. Composition/information on ingredients

Einecs no.	Substances	Classification	w/w%
265-185-4	Naphtha (petroleum), hydrodesulfurized heavy	Xn;R65-48/20 R66	60-100
<i>Please see section 16 for the full text of the R-phrases</i>			

3. Hazards identification

Harmful: danger of serious damage to health by prolonged exposure through inhalation. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

Additional information

Prolonged or repeated inhalation of vapours may damage the central nervous system.

4. First aid measures

Inhalation

Seek fresh air. Seek medical advice if symptoms persist.

Ingestion

Rinse mouth thoroughly and then drink plenty of water. Do not induce vomiting. If vomiting occurs keep head low so that stomach contents do not enter lungs. Seek medical advice immediately.

Skin

Wash skin with water and soap. Seek medical advice if symptoms persist.

Eyes

Rinse immediately with water (preferably using eye wash) for at least 5 minutes. Open eyes wide. Remove any contact lenses. Seek medical advice if irritation persists.

Burns

Flush with water until pain ceases. Remove clothing that is not stuck to the skin – seek medical advice/transport to hospital. If possible, continue flushing until medical attention is obtained.

Other information

When obtaining medical advice, show the safety data sheet or label. Symptoms: See section 11.

5. Fire-fighting measures

Extinguish with powder, foam, carbon dioxide or water mist. Do not use water spray, as it may spread the fire. Use water or water mist to cool non-ignited stock. Remove containers from the danger area if this is possible without risk. Do not inhale vapours and flue gases - seek fresh air.

6. Accidental release measures

Use the same personal protection as for item 8. Mop up spillage with a cloth. Sweep/pick up spill for possible reuse or place in suitable waste containers. For information on disposal please see item 13.

Prepared on: 09-09-2005/MBM
Replaces: 18-12-2003

Teak Oil
(290/1290/30290)

7. Handling and storage

Handling

Please see item 8 for information on precautions by use and personal protection.

Storage

Store safely, out of reach of children and not together with food, animal feeding stuffs, medicines, etc. To be kept frost-free in a tightly closed packaging.

8. Exposure controls/ personal protection

Precautions for use

Work must be done with efficient process ventilation (e.g. local extractor fan). There must be access to running water and eye wash. Wash hands before breaks and toilet visits and after work. Smoking and naked flames prohibited.

Respiratory protection

In case of insufficient ventilation, wear respiratory protective equipment with filter A2.

Gloves and protective clothing

Gloves of plastic or rubber are recommended.

Eye protection

Wear eye protection on risk of splashes in eyes.

Occupational exposure limits

Contains no substances subject to reporting requirements.

9. Physical and chemical properties

Appearance: Fluid/creme

Flash point: >65 °C:

10. Stability and reactivity

The product is stable if used in accordance with supplier's instructions.

Chemtox A/S, Pakhustorvet 4, DK-6000 Kolding Tlf.: +45 75508811, Fax: +45 75508810, E-mail: Chemtox@Chemtox.dk

Prepared on: 09-09-2005/MBM
Replaces: 18-12-2003

Teak Oil
(290/1290/30290)

11. Toxicological information

Acute

Inhalation

Harmful: danger of serious damage to health on prolonged exposure through inhalation. The product releases vapours from organic solvents. At high concentrations vapours may cause headaches, dizziness, intoxication and possible unconsciousness.

Ingestion

May irritate mucous membranes in mouth and stomach/intestine. May cause chemical pneumonia if the product is ingested or vomited.

Skin contact

Degreases and dries skin. Repeated exposure may cause skin dryness or cracking.

Eye contact

May irritate the eye.

Long-term effects

May cause damage to the central nervous system

Prolonged or repeated inhalation of vapours may damage the central nervous system.

12. Ecological information

Avoid discharge into drains or surface water.

13. Disposal considerations

Collect spills and waste in closed and sealed containers and send to the local disposal facility for chemical waste.

EWC code: Depending on line of business and use e.g. 20 01 13

Wiping cloths with organic absorbing solution:

EWC code: 15 02 02 absorbing solutions, filter materials, wiping cloths and protection clothes polluted with dangerous cargo.

14. Transport information


The product is not comprised by the rules of dangerous goods on road or sea according to ADR and IMDG.

Chemtox A/S, Pakhustorvet 4, DK-6000 Kolding Tlf.: +45 75508811, Fax: +45 75508810, E-mail: Chemtox@Chemtox.dk

Prepared on: 09-09-2005/MBM
Replaces: 18-12-2003

Teak Oil
(290/1290/30290)

15. Regulatory information



Harmful

Hazard designation: Harmful

Hazard symbols: Xn

Contains

Naphtha (petroleum), hydrodesulfurized heavy

R-phrases

Harmful: danger of serious damage to health by prolonged exposure through inhalation. (R48/20)

Harmful: may cause lung damage if swallowed. (R65)

Repeated exposure may cause skin dryness or cracking. (R66)

S-phrases

Keep out of reach of children. (S2)

Do not breathe vapour. (S23)

Avoid contact with the skin. (S24)

If swallowed, do not induce vomiting, seek medical advice immediately and show this container or label. (S62)

Other labelling

Tactile warning device.

Chemtox A/S, Pakhustorvet 4, DK-6000 Kolding Tlf.: +45 75508811, Fax: +45 75508810, E-mail: Chemtox@Chemtox.dk

Prepared on: 09-09-2005/MBM
Replaces: 18-12-2003

Teak Oil
(290/1290/30290)

16. Other information

Restrictions on use

None

Training requirement

No special training is necessary but a thorough knowledge of this safety data sheet is assumed.

Packaging

250 ml, 1 l and 5 L.

Sources used

ADR 2005 edition and IMDG 2004 edition.

Approved classification and labelling guide (fifth edition) 2002.

Approved Supply List (seventh edition): Information approved for the classification and labelling of substances and preparations dangerous for supply. Chemicals (Hazard Information and Packaging for Supply) Regulations 2002, 29. ATP.

EH40/2005 Workplace exposure limits.

Commission decision as regards the list of wastes 2001/118/EC.

The compilation of safety data sheets (third edition) 2002.

Other information

This safety data sheet was prepared on the basis of the information from the supplier on the product (e.g. material data sheets and the like).

Full text of the R-phrases in section 2

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R65 Harmful: May cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

Amendments have been made in the following sections

Item 1, 4, 8 and 16.

Chemtox A/S, Pakhustorvet 4, DK-6000 Kolding Tlf.: +45 75508811, Fax: +45 75508810, E-mail: Chemtox@Chemtox.dk (Made in Toxido®)