

SAFETY DATA SHEET

MATERIAL SAFETY DATA SHEET

Last changed: 28/01/2004

Internal No.:

Replaces date:

99 STERLING STRYGEST

1. IDENTIFICATION OF PRODUCT AND COMPANY

 Approved for use **TRADE NAME** 99 STERLING STRYGEST**APPLICATION****FORMULA****Art. no.**

0312208.8360

Producer/importer**Company** Sterling Polish Company A/S**Address** Nybrovej 95**Postal code** 2820 Gentofte**Country** DK**Internet** www.sterlingpolish.com**Telephone****Fax**

Emergency Telephones

Emergency Phone	Information
	112

2. COMPOSITION/INFORMATION ON INGREDIENTS

No	Ingredient name	EC No.	CAS No.	Conc. (wt%)	Classification
1	WATER	231-791-2	7732-18-5	50 - 80 %	-
2	OXIDIZED STARCH ACETATE	-	68187-08-6	1 - 10 %	
4	BUTANE	203-448-7	106-97-8	5 - 15 %	F+,R12
5	PROPANE	200-827-9	74-98-6	1 - 5 %	F+,R12

Legend: T+=Very toxic, T=Toxic, C=Corrosive, Xn=Harmful, Xi=Irritant, E=Explosive, O=Oxidising, F+=Extremely flammable, F=Highly flammable, N=Dangerous for the environment

3. HAZARDS IDENTIFICATION



Extremely flammable

GENERAL

PRESSURIZED CONTAINER.

FIRE AND EXPLOSION

EXTREMELY FLAMMABLE.

SAFETY DATA SHEET

MATERIAL SAFETY DATA SHEET

Last changed: 28/01/2004

Internal No.:

Replaces date:

99 STERLING STRYGEST

4. FIRST AID MEASURES

INHALATION

Fresh air and rest.

SKIN CONTACT

Wash the skin with water and soap.

EYE CONTACT

Rinse immediately with water for 10-15 minutes. Keep the eyes open. If symptoms persist: To hospital as soon as possible.

INGESTION

Drink water.

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Extinguish with powder/carbon dioxide/foam.

FIRE AND EXPLOSION HAZARDS

Must not be exposed to direct sunlight or temperatures exceeding + 50° C. Do not puncture or incinerate aerosol cans, not even if the container is empty. Don't spray in the direction of open flame or red-hot material.

OTHER INFORMATION

Containers near fire must be moved and/or cooled with water.

6. ACCIDENTAL RELEASE MEASURES

OTHER INFORMATION

Wipe up spill with paper or rag.

7. HANDLING AND STORAGE

HANDLING PRECAUTIONS

Keep out of reach of children.

HANDLING ADVICE

None

STORAGE

Must not be exposed to direct sunlight or temperatures exceeding +50°C.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

EYE PROTECTION

Not necessary.

HAND PROTECTION

Not necessary.

PROTECTIVE CLOTHING

Not necessary.

SAFETY DATA SHEET

MATERIAL SAFETY DATA SHEET

Last changed: 28/01/2004

Internal No.:

Replaces date:

99 STERLING STRYGEST**9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical State Aerosol.
Colour Colourless.
Odour Perfume
Solubility Water.

10. STABILITY AND REACTIVITY**STABILITY**

Stable with normal handling.

11. TOXICOLOGICAL INFORMATION**EYE CONTACT**

May cause: Stinging.

12. ECOLOGICAL INFORMATION**OTHER INFORMATION**

The product is not classified as "Dangerous for the environment".

13. DISPOSAL CONSIDERATIONS**GENERAL REGULATIONS**

Empty containers can be recycled as metal scrap (not containers that has been filled with products that are classified as dangerous for the environment). Filled containers are treated as hazardous waste.

CATEGORY OF WASTE

Filled containers are treated as hazardous waste.

14. TRANSPORT INFORMATION

Classified as Dangerous Goods: Yes No N/A

UN No.: 1950

PROPER SHIPPING NAME

Aerosols.

ADR/RID

Class:	2, 5F	Packing group:	
Danger form:	2.1		

IMDG

Class:	2	Packing group:	
Sub Risk:	no	EMS:	F-D, S-U
Marine Pollutant:	no		

SAFETY DATA SHEET

MATERIAL SAFETY DATA SHEET

Last changed: 28/01/2004

Internal No.:

Replaces date:

99 STERLING STRYGEST**IATA**

Class:	2.1	Packing group:	
Sub Risk:	no		
Label:	2.1		

OTHER INFORMATION

Aerosols may be carried domestically as ordinary goods (LQ) as long as each package does not exceed 30kg in cardboard box or 20 kg on tray with shrink wrapping. Each collie shall be marked "UN 1950".

15. REGULATORY INFORMATION

Extremely flammable

EC-Label

No



Yes



N/A

R-PHRASES

R12 - Extremely flammable.

S-PHRASES

S2-Keep out of reach of children.

S3.6-Must not be exposed to temperatures exceeding +50°C.

S16-Keep away from sources of ignition - No smoking.

S23.3-Do not breathe vapour.

S51-Use only in well ventilated areas.

16. OTHER INFORMATION**LIST OF RELEVANT R-PHRASES**

Nr.	R-Phrase text
R12	Extremely flammable.

TRAINING ADVICE

The information in this MSDS shall be available to those who handle the product.

ISSUED:

28/01/2004

REVISION HISTORY

Version	Rev. date	Responsible	Changes
0.0.1	28/01/2004	Josefine Sjöblom	nytt-new

SDS prepared by**Company** Aerosol Scandinavia AB

Name	E-mail	Phone (work)
Josefine Sjöblom		+46 8 511 888 24